

## SECTION 06424 - PROTECTIVE SURFACING

## PART 1 - GENERAL

## 1.1 SUMMARY

- A. Section Includes:
  - 1. Interior rigid sheet protective wall covering.
  - 2. Owner furnished interior rigid sheet protective wall covering.
- B. Related Requirements:
  - 1. Section 09250 - Gypsum Board: Substrate for protective surfacing.
  - 2. Appendix A – Products and Work by Owner or Separate Contractor.

## 1.2 REFERENCES

- A. The publications listed below form a part of this specification to the extent referenced. Publications are referenced within the text by the basic designation only.
- B. ASTM International (ASTM):
  - 1. ASTM E 84 - Test Method for Surface Burning Characteristics of Building Materials.
  - 2. ASTM D1308 - Standard Test Method for Effect of Household Chemicals on Clear and Pigmented Organic Finishes.
  - 3. ASTM F476 - Standard Test Methods for Security of Swinging Door Assemblies.

## 1.3 QUALITY ASSURANCE

- A. Manufacturer's Qualifications: Not less than 5 years experience in the production of specified product.
- B. Installer qualifications: Not less than 3years experience in installation of similar product/system, as required for this project.
- C. Fire Performance Requirements:
  - 1. Surface Burning Characteristics: Conform to the following in accordance with ASTM E 84.
    - a. Flame Spread: 25 or less.
    - b. Smoke Density: 450 or less.
- D. Impact Strength Requirements:
  - 1. Tested in accordance with and meets or exceeds the applicable provisions of ASTM F 476.
- E. Chemical and Stain Resistance Requirements:
  - 1. Tested in accordance with and meets or exceeds ASTM D 1308.

## 1.4 DELIVERY, STORAGE AND HANDLING

- A. Transport, handle, store, and protect products in compliance with the requirements of Section 01600.
- B. Store in clean, dry, enclosed, and secure storage area. Store flat and in accordance with manufacturer's published requirements.
- C. Protect protective surfacing products and accessories, especially adhesive, from freezing temperatures, excessive heat, temperature fluctuations, humidity and moisture penetration.

## 1.5 PROJECT CONDITIONS

- A. Store material in an environment of 65-75°F for at least 24 hours prior to beginning the installation.
- B. Installation areas shall be enclosed and weatherproofed before installation commences.

## PART 2 - PRODUCTS

### 2.1 OWNER FURNISHED PRODUCTS

- A. Owner's Supplier will furnish the following as specified in Appendix A (Section 06424) for installation by Contractor.
  - 1. PS-7: Gray pattern rigid sheet protective wall covering panel.

### 2.2 RIGID SHEET PROTECTIVE WALL COVERING

- A. Manufacturer:
  - 1. Impact Specialties, Kennesaw, GA. Contact: Walmart National Account (888) 424-6287, [ORDERS@impactspecialties.com](mailto:ORDERS@impactspecialties.com)
- B. Description:
  - 1. PVC-free polyester blend compound, high impact, rigid sheet.
  - 2. Thickness: .040 inch.
  - 3. Sheet Size: 4 feet by 8 feet or 4 feet by 10 feet according to manufacturer's part designations below.
  - 4. Texture: Suede.
  - 5. Color:
    - a. PS-1: Walmart Blue. Impact Specialties Part No. WMWC40ES410S601.
    - b. PS-3: Brushed Silver. Impact Specialties Part No. CSCW40410378N.
    - c. PS-4: Glowing Ember. Impact Specialties Part No. CSWC40481234N.
    - d. PS-5: Fresh Linen. Impact Specialties Part No. CSWC40481233N.
    - e. PS-6: Butterfield. Impact Specialties Part No. CSWC404101331N.

### 2.3 ACCESSORIES

- A. Adhesive: Spray Lock Wall Panel Adhesive, as manufactured by Interlock Industries, Inc., Chattanooga, TN, (479) 721-5431.
- B. Trim: Ecoshield extrusions by Impact Specialties. Color: to match wall covering panel.
  - 1. Inside Corner: Manufacturer's standard.
    - a. Impact Specialties Part No. WMWC40IS601 (Walmart Blue).
    - b. Impact Specialties Part No. CSWC40IS378N (Brushed Silver).
    - c. Impact Specialties Part No. CSWC40IS1234N (Glowing Ember).
    - e. Impact Specialties Part No. CSWC40IS1233N (Fresh Linen).
  - 2. High Impact Outside Corner: SSM-20 Suede Texture, 4 feet 1 inch long with caps (including retainer and fasteners).
    - a. Impact Specialties Part No. WMSSM20ESS601 (Walmart Blue).
    - b. Impact Specialties Part No. CSSSM204F374N (Brushed Silver).
    - c. Impact Specialties Part No. CSSSM20411234N (Glowing Ember).
    - d. Impact Specialties Part No. CSSSM20411233N (Fresh Linen).
  - 3. Low Impact Outside Corner: VA-200, 4 feet 1 inch long.
    - a. Impact Specialties Part No. CSVA2004FNT601N (Walmart Blue).
    - b. Impact Specialties Part No. CSVA20041108N (Black).
  - 4. Top Cap: Wainscot Molding.
    - a. Impact Specialties Part No. CSWC40WT601N (Walmart Blue).
    - b. Impact Specialties Part No. CSWC40WT1234N (Glowing Ember).
    - c. Impact Specialties Part No. CSWC40WT1233N (Fresh Linen).
    - d. Impact Specialties Part No. CSWC40WT1331N (Butterfield).

- 5. Vertical Seam Trim:
  - a. Impact Specialties Part No. CSWC40VT601N (Walmart Blue).
  - b. Impact Specialties Part No. CSWC40VT1234N (Glowing Ember).
  - c. Impact Specialties Part No, CSWC40VT1233N (Fresh Linen).
  - d. Impact Specialties Part No, CSWC40VT1331N (Butterfield).
  
- C. Caulk: Color-matched and furnished by manufacturer.
  - 1. Impact Specialties Part No. WMCAULK601 (Walmart Blue).
  - 2. Impact Specialties Part No. CSCAULK374 (Brushed Silver).
  - 3. Impact Specialties Part No. CSCAULK1234 (Glowing Ember).
  - 4. Impact Specialties Part No. CSCAULK1233 (Fresh Linen).
  - 5. Impact Specialties Part No. CACAULK1331 (Butterfield).

## PART 3 - EXECUTION

### 3.1 EXAMINATION

- A. Examine surfaces and adjacent areas where protective wall covering will be installed and verify that substrates are flat, clean, dry, solid, and free from coatings and defects detrimental to installation. Verify that surfaces conform to product manufacturer's requirements for substrate conditions.

### 3.2 PREPARATION

- A. Where new protective surfacing is to be installed, remove existing surfacing and/or finishes to base substrate prior to installation of new. Installation of new protective surfacing over existing is not acceptable, no exceptions.
- B. Prepare substrate for protective wall covering installation in accordance with manufacturer's published instructions and recommendations.
- C. View manufacturer's installation video prior to start of installation.

### 3.3 INSTALLATION

- A. Install protective wall covering and accessories, including trim, in accordance with manufacturer's published instructions and video. Use manufacturer's recommended adhesive, as specified above. Follow the manufacturer's installation video except as otherwise instructed by the manufacturer.
  - 1. Install inside corner trim using included adhesive tape.
  - 2. Install outside corner trim using included retainers, fasteners and end caps.
- B. Relative humidity shall not exceed 80% at time of installation.
- C. Apply using adhesive specified.
- D. Apply caulk at butt joints as required to fill gaps.
- E. Maintain temperature between 65-75°F for at least 48 hours after the installation.

### 3.4 CLEANING

- A. Immediately upon completion of installation, clean protective surfacing and accessories in accordance with manufacturer's recommended cleaning method.
- B. Remove surplus materials, rubbish and debris resulting from installation as work progresses and upon completion of work.

3.5 PROTECTION

- A. Protect installed protective surfacing from subsequent construction activities. Use materials that may be easily removed without leaving residue or permanent stains.

END OF SECTION