EQUIVAL	ENT NOW	IINAL PIF	PE SIZE		
PLAN SIZE	AQUATHERM	AQUATHERM	PEX		
(COPPER)	HOT WATER	COLD WATER			
1/2"	1/2"	1/2"	1/2"		
3/4"	3/4"	3/4"	1"		
1"	1"	1"	1 1/4"		
1 1/4"	1 1/2"	1 1/4"	1 1/2"		
1 1/2"	2"	1 1/2"	2"		
2"	2 1/2"	2"	NA		
2 1/2"	3"	2 1/2"	NA		
3"	3 1/2"	3"	NA		
4"	6"	4"	NA		
NOTE: REFER	TO SPECIFICATI	ONS FOR APPR	OVED		

MANUFACTURERS.

ALL PROD	DUCTS ON THIS SCHEDUL			D BY OW			XTURE SCHED ACTOR. REFER TO SPECE CATALOG		NOTES
SS1	SERVICE	CW 3/4"	HW 3/4"	WASTE		STERN-	NUMBER SB-800	CHROME PLATED FAUCET WITH INTEGRAL CHECK VALVES,	В
	SINK (TERRAZZO)					WILLIAMS FIAT TSB-200, ACORN		HOSE, BRACKET AND MOP HANGER.	
	24" × 24" × 12"					897-020JKRCF ADAPTI	ERS), ZURN Z843M1—CS	RD SUPPLY ARMS & CONNECT (2) GCJKCP SUPPLY ARMS USING (2) S, T&S BRASS B-0665-BSTP W/ ETERNA CARTRIDGES & SPRING CHECKS 832-AA, ACORN KH36	
SS4	SERVICE	3/4"	3/4"	3"	2"	· · · · · · · · · · · · · · · · · · ·	WILLIAMS T-40, FIAT 88 HL-1810-LB	· · · · · · · · · · · · · · · · · · ·	В
	SINK (TERRAZZO)					WILLIAMS FIAT TSB-3000, ACORI		HOSE, BRACKET AND MOP HANGER.	
	24" x 24" X 12" 6" DROP FRONT					897-020JKRCF ADAPTI	ERS), ZURN Z843M1—CS	RD SUPPLY ARMS & CONNECT (2) GCJKCP SUPPLY ARMS USING (2) S, T&S BRASS B-0665-BSTP W/ ETERNA CARTRIDGES & SPRING CHECKS 832-AA, ACORN KH36	
SS5	SERVICE	3/4"	3/4"	3"	2"	MOP HANGER: STERN STERN	WILLIAMS T-40, FIAT 88 HL-1910-LB	89-CC, ACORN KMH CHROME PLATED FAUCET WITH INTEGRAL CHECK VALVES, HOSE,	В
	SINK (TERRAZZO) 32" × 32" X 12"					WILLIAMS FIAT TSB-3001, ACORN		BRACKET, MOP HANGER, LINT BASKET, & S.S. CAP ON ALL SIDES RD SUPPLY ARMS & CONNECT (2) GCJKCP SUPPLY	
	6" DROP FRONT					ARMS USING (2) 897-	020JKRCF ADAPTERS),	P W/ ETERNA CARTRIDGES & SPRING CHECKS	
SS30	ACORNVAC	<u> </u>		3"	2"		N WILLIAMS T-35, FIAT WILLIAMS T-40, FIAT 88 MTB-3624		
3330	MOP SINK (TERRAZZO)					WILLIAMS FIAT	TTB-3624	PLUMBING SYSTEM. MOP SINK ONLY, NO FAUCET REQUIRED	
SS31	36" X 24" X 10" SERVICE	3/4"	3/4"	3"	2"	ACORN STERN-	TRH-362410 SBC-1700-LB	CHROME PLATED FAUCET WITH INTEGRAL CHECK VALVES,	В
	SINK (TERRAZZO) 24" × 24" X 12"					WILLIAMS FIAT TSBC-1610, ACOR		HOSE, BRACKET AND MOP HANGER. RD SUPPLY ARMS & CONNECT (2) GCJKCP SUPPLY ARMS USING (2)	
	6" CORNER DROP FRONT					897-020JKRCF ADAPTI	ERS), ZURN Z843M1—CS	S, T&S BRASS B-0665-BSTP W/ ETERNA CARTRIDGES & SPRING CHECKS 832-AA, ACORN KH36	
SS32	SERVICE	3/4"	3/4"	3"	2"	STERN-	WILLIAMS T-40, FIAT 88 SBC-1725-LB	CHROME PLATED FAUCET WITH INTEGRAL CHECK VALVES, HOSE,	В
	SINK (TERRAZZO) 32" × 32" X 12"					WILLIAMS FIAT TSBC-1611, ACOR FAUCET: CHICAGO 897		BRACKET, MOP HANGER, LINT BASKET, & S.S. CAP ON ALL SIDES RD SUPPLY ARMS & CONNECT (2) GCJKCP SUPPLY	
	6" CORNER DROP FRONT					ARMS USING (2) 897- ZURN Z843M1-CS, T&S	020JKRCF ADAPTERS), S BRASS B-0665-BSTF	P W/ ETERNA CARTRIDGES & SPRING CHECKS	
SS33	SERVICE	3/4"	3/4"	3"	2"	·	N WILLIAMS T-35, FIAT WILLIAMS T-40, FIAT 88 HL2100	832-AA, ACORN KH36 89-CC, ACORN KMH CHROME PLATED FAUCET WITH INTEGRAL CHECK VALVES, HOSE,	В
3333	SINK (TERRAZZO)	37+	3/4		2	WILLIAMS FIAT TSB-3003, ACORI		BRACKET, MOP HANGER, LINT BASKET, & S.S. CAP ON ALL SIDES	
	36" x 24" X 12" DROP FRONT					ARMS USING (2) 897-	020JKRCF ADAPTERS),	RD SUPPLY ARMS & CONNECT (2) GCJKCP SUPPLY	
						HOSE/BRACKET: STERN		P W/ ETERNA CARTRIDGES & SPRING CHECKS 832-AA, ACORN KH36 89-CC ACORN KMH	
SS34	SERVICE SINK	3/4"	3/4"	3"	2"	KOHLER AMERICAN	6719 7692.000	CHROME PLATED FAUCET WITH INTEGRAL CHECK VALVES, & S.S. RIM GUARD.	
	CAST IRON W/ ENAMEL FINISH							RD SUPPLY ARMS & CONNECT (2) GCJKCP SUPPLY	
	WALL MOUNT						•	P W/ ETERNA CARTRIDGES & SPRING CHECKS	
SS35	SERVICE						# 7798.030 3" CAST II		
	SINK FIBERGLASS					FAUCET: CHICAGO 891	-E2CP		
S2	FLOOR MOUNT SINK (PHARMACY)	1/2"	1/2"	2"	1 1/2"	DAYTON	D-12521	4 HOLES, 2.2 GPM FLOW RESTRICTOR AND AERATOR	C,D
	1—COMPARTMENT STAINLESS STEEL		, –		, –	BY ELKAY KOHLER K-3348			-,-
S3	SINK (LOUNGE) 2-COMPARTMENT	1/2"	1/2"	2"	1 1/2"	ELKAY	LRAD2918	K15071-P, DRAIN: ELKAY LK-35, KOHLER K8801 4 HOLES, DROP IN STYLE, 2.2 GPM FLOW RESTRICTOR, AERATOR AND SPRAY HOSE, 6 1/2" MAXIMUM DEPTH	C,D
	STAINLESS STEEL						LKAY LK-1001, JUST J		
L40	LAVATORY	1/2"	1 '	1 1/2"	1 1/2"		K-2005	FAUCET: SPEAKMAN SC-3084 CENTERSET FAUCET,	G, H
			(T)			AMERICAN STANDARD TOTO	0355.012 LT307.4	GRID STRAINER WITH TAILPIECE, P-TRAP WITH CLEANOUT, STOP VALVES, SS BRAIDED WATER SUPPLIES AND ESCUTCHEONS. PROVIDE THERMOSTATIC MIXING VALVE FOR L41.	
L41	LAVATORY	1/2"	1/2"	1 1/2"	1 1/2"		K-2005 0355.012	CARRIER: JOSAM 17100 (FLOOR MOUNT), WADE W-520 (FLOOR MOUNT) OR JOSAM 17120 (WALL MOUNT).	F, G, H
						STANDARD TOTO	LT307.4	LAVATORY ENCLOSURE: TRUEBRO LAV—SHIELD 2018 L41 ASSE 1070 THERMOSTATIC MIXING VALVE: ZURN ZW3870XLT	
EW1	EYEWASH		1/2" (T)	1 1/2"	1 1/4"	BRADLEY	S19-220	SET TO 105°F. WALL MOUNTED, GALVANIZED STEEL PIPE, CHROME PLATED BRASS VALVE, YELLOW PLASTIC BOWL WITH DUST COVER, 304	A
								SS HANDLE. PROVIDE P-TRAP AND TAILPIECE WHERE APPLICABLE ON PLANS.	
EW2	EYEWASH		1 '	1 1/2"	1 1/4"	1	NCON 01030401, GUARD S19-224-ADA	WALL MOUNTED, GALVANIZED STEEL PIPE, CHROME PLATED	A
			(T)					BRASS VALVE, YELLOW PLASTIC BOWL WITH DUST COVER, 304 SS HANDLE. PROVIDE P-TRAP AND TAILPIECE WHERE APPLICABLE ON PLANS.	
PVB2	PRESSURE					SPEAKMAN SE-580-AL	DA LF008PCQT	LEAD FREE HIGH-HAZARD ANTI-SIPHON, ANTI-SPILL VACUUM BREAKER	
PVB30	VACUUM BREAKER PRESSURE VACUUM BREAKER					WATTS	LFN36N1	AND INLET AND OUTLET SHUT-OFF VALVES. CONFORM TO ASSE 1056. LEAD FREE BRASS WATER SERVICE VACUUM RELIEF VALVE OUTLET SHUT-OFF VALVES. CONFORM TO ASSE 1020	
PRV	VACUUM BREAKER WATER					ZURN 12-VR10XL AF	POLLO 37-LF202-01 LF223	LEAD FREE BRONZE BODY VALVE WITH SHUT-OFF VALVES FOR SIZES	
	PRESSURE REGULATOR							UP TO 2-1/2", CAST IRON BODY FOR 3" AND ABOVE. MAXIMUM OPERATING PRESSURE OF 200 PSI. CONFORM TO ASSE 1003.	
TMV	THERMOSTATIC MIXING	3/4"	3/4"			WILKINS 500XL LAWLER	570	LEAD FREE HEAVY CAST BRONZE BODY VALVE, ROUGH BRONZE FINISH, BIMETAL THERMOSTAT OR THERMAL MOTOR, INTEGRAL	
	VALVE							CHECK VALVES, LIMIT STOP SET AT 105 °F UNLESS NOTED OTHER— WISE. MINIMUM FLOW RATE 0.5 GPM. CONFORM TO ASSE 1017/1070.	
TMV30	THERMOSTATIC					LEONARD 370-LF LAWLER	802	LEAD FREE HEAVY CAST BRONZE BODY VALVE, ROUGH BRONZE	
	MIXING VALVE							FINISH, BIMETAL THERMOSTAT OR THERMAL MOTOR, CHECK STOPS WITH STRAINERS, AND LIMIT STOP SET, FIELD SET AT TEMPERATURE INDICATED ON PLAN. MIN FLOW RATE 2.0 GPM.	
						LEONARD TM-186-501	5-PRV	CONFORM TO ASSE 1017.	
ETMV	EMERGENCY THERMOSTATIC					BRADLEY	S19-2000	HEAVY CAST BRONZE BODY VALVE, ROUGH BRONZE FINISH, BIMETAL THERMOSTAT OR THERMAL MOTOR, INTEGRAL CHECK	
	MIXING VALVE					LEONARD TA-300, POV	 WFRS FS150	STOPS AND VANDAL RESISTANT LIMIT STOP SET AT 65° F. MINIMUM FLOW RATE 1.0 GPM.	
ETMV2	EMERGENCY THERMOSTATIC					BRADLEY	S19-2100	HEAVY CAST BRONZE BODY VALVE, ROUGH BRONZE FINISH, BIMETAL THERMOSTAT OR THERMAL MOTOR, INTEGRAL CHECK	
	MIXING VALVE					DOWERS TO		STOPS AND VANDAL RESISTANT LIMIT STOP SET AT 65°F MINIMUM FLOW RATE 2.0 GPM.	
HR1	HOSE REEL	1/2"				POWERS ES-P-ETV200 COX REEELS / CCR-0426-1	REELCRAFT / 7850-OPL-SW578	SELF-RETRACTING OPEN REEL WITH 50' 1/2" ID YELLOW WATER HOSE.	
						(800) 269-7335	(800) 444–3134		

|--|--|--|

^{1.} THIS SCHEDULE IS COMPREHENSIVE. ALL MARKS MAY OR MAY NOT BE USED ON THE PLANS. 2. SUBSTITUTIONS NOT PERMITTED. REF SPECIFICATIONS FOR APPROVED MANUFACTURERS OF THE FOLLOWING TRIM AND ACCESSORIES;

					Y OWNER	AND INSTALLED BY	BING FIXTURE CONTRACTOR. REFER T	O SPECIFICATIONS.	
IARK	FIXTURE	CW	RANCH S	SIZES (MI WASTE	 	MANUFACTURER	CATALOG NUMBER	TRIM	NOT
WC1	WATER CLOSET (FLOOR MOUNT)	1 1/4"		4"	2"	TOTO SLOAN		FLUSH VALVE: TOTO TET1LA32#CP-WR - 1.28 GPF SENSOR OPERATED SELF GENERATING POWER SYSTEM WITH MANUAL OVERRIDE AND	
VC2	WATER CLOSET HANDICAPPED	1 1/4"		4"	2"	TOTO SLOAN	CT705ELN ST-2029-A	VANDAL RESISTANT SET SCREW ESCUTCHEON AND STOP CAP. ELONGATED SEAT: BEMIS 1055SSC, MAINLINE ML 1055SSC CAST IRON FLOOR FLANGE: ZURN CF-2984-CI4, TYLER 2-252TS2,	D
VC3	(FLOOR MOUNT) WATER CLOSET	1 1/4"		4"	2"	TOTO	CT708E	WITH "NO SEEP" WAX RING AND BRASS ANCHOR BOLTS. FLUSH VALVE: TOTO TET1LA32#CP-WR - 1.28 GPF SENSOR OPERATED	
C4	(WALL MOUNT) WATER CLOSET HANDICAPPED (WALL MOUNT)					SLOAN	ST-2059-A	SELF GENERATING POWER SYSTEM WITH MANUAL OVERRIDE AND VANDAL RESISTANT SET SCREW ESCUTCHEON AND STOP CAP. ELONGATED SEAT: BEMIS 1055SSC, MAINLINE ML 1055SSC	D
30	WATER CLOSET	1/2"		4"	2"	ТОТО	CST744E	1.28 GPF FLUSH TANK W/ LOCKING COVER ELONGATED SEAT: BEMIS 1055SSC, MAINLINE ML 1055SSC CAST IRON FLOOR FLANGE: JONESPEC CF-2984-C14, TYLER	
231	WATER CLOSET HANDICAPPED	1/2"		4"	2"	ТОТО	CST744EL	2-252, WITH "NO SEEP" WAX RING AND BRASS ANCHOR BOLTS. SUPPLY LINE: STAINLESS STEEL BRAIDED HOSE, 1/4 TURN BALL VALVE STOP.	
C1	WATER CLOSET CARRIER			4"	2"	JOSAM WADE	12694 310ND	ADJUSTABLE COATED CAST IRON SHORT BARREL 4" NO HUB FITTING WITH 2" NO HUB VENT, ABS EXTENSION WITH TEST CAP,	
.411	DOUBLE HORIZONTAL	ANDICAD	LIFICUT	ODTION	AC INDIC	NATED BY THE FOLLO	MINO CHEEIVEC. JOCAN	CHROME PLATED HARDWARE, NEOPRENE FITTING AND FIXTURE GASKETS, AND HUSKY SD4000 COUPLINGS.	
:1H ::2	WATER CLOSET	ANDICAP	HEIGH I	4"	AS INDIC	JOSAM JOSAM	WING SUFFIXES: JOSAM 12684	: -35, WADE: -H ADJUSTABLE COATED CAST IRON SHORT BARREL 4" NO HUB FITTING	
HT)	CARRIER				_	WADE	310NR-UA	WITH 2" NO HUB VENT, FACTORY—TAPPED 2" NO HUB URINAL	
C3 :FT)	SINGLE HORIZONTAL			4"	2"	JOSAM WADE	12674 310NL-UA	CONNECTION, ABS EXTENSION WITH TEST CAP, CHROME PLATED HARDWARE, NEOPRENE FITTING AND FIXTURE GASKETS, AND HUSKY SD4000 COUPLINGS. FLOW DIRECTION (RIGHT OR LEFT) IS FROM	
	CC2 CARRIER WITH H	 ANDICAP	HEIGHT	OPTION	AS INDIC		OWING SUFFIXES: JOSAN	SEATED FIXTURE USER'S POINT OF REFERENCE.	
			1			· · · · · · · · · · · · · · · · · · ·	WING SUFFIXES: JOSAN	,	
R1 R2	URINAL	3/4"		2"	1 1/2"	ZURN AMERICAN STANDARD	Z5798 6590.525	HIGH EFFICIENCY URINAL (HEU) SYSTEM: CHINA URINAL AND 0.125 GPF TURBINE OR BATTERY POWERED, WALL MOUNTED SENSOR OPERATED FLUSH VALVE WITH MANUAL OVERRIDE AND VANDAL RESISTANT SET	
	HANDICAPPED					ТОТО	UT105U TEU1UA12#CP	SCREW ESCUTCHEON AND STOP CAP.	
C1	URINAL CARRIER					JOSAM WADE	17560-UR 400,AM11	FLOOR MOUNTED WITH HANGER AND BEARING PLATES, WELDED FEET, ADJUSTABLE SUPPORTING RODS, STRUCTURAL UPRIGHTS, AND CHROME PLATED TRIM.	
.1	LAVATORY		1/2" (T)	1 1/2"	1 1/2"	KOHLER AMERICAN	K-2005 0355.012	FAUCET: TOTO TEL3LS-10 - 0.5 GPM SENSOR OPERATED SELF- GENERATING POWER SYSTEM, STANDARD SPOUT, 4" COVER	
						STANDARD		PLATE, GRID STRAINER WITH TAILPIECE, P-TRAP WITH CLEANOUT,	
2	LAVATORY	1/2"	1 /2"	1 1/2"	1 1/2"	TOTO KOHLER	LT307.4 K-2005	STOP VALVES, SS BRAIDED WATER SUPPLIES AND ESCUTCHEONS. PROVIDE THERMOSTATIC MIXING VALVE FOR L2.	Δ
_	LAVATORT	'/ -	'/ =	' '/ 4	' '/ 4	AMERICAN	0355.012	CARRIER: JOSAM 17100, WADE W-520.	7
						STANDARD TOTO	LT307.4	LAVATORY ENCLOSURE: TRUEBRO LAV—SHIELD 2018 L2 ASSE 1070 THERMOSTATIC MIXING VALVE: ZURN ZW3870XLT	
 5	CTAINII FCC	1/2"	1 /0"	1 1/2"	1 1 /0"	CDIECINI	H68-128	SET TO 105°F.	
O .	STAINLESS STEEL SINK (TLE)	1/2	1/2	1 1/2	1 1/2	GRIFFIN	H68-128	FAUCET: GRIFFIN FG-105 WITH FA-100 WRIST BLADES AND WA-151 GRID STRAINER, TAILPIECE, MCGUIRE PW2150 PRE-WRAPPED P-TRAP WITH TAILPIECE, STOP AND SUPPLY COVERS, SS BRAIDED WATER SUPPLIES, STOP VALVES AND ESCUTCHEON.	
18	LAVATORY DECK 3-STATION RIGHT TRASH		1/2" (3, T)	,	1 1/2"	LEVANTINA	Q3303RT	CARRIER: JOSAM 17560, WADE W-520 LEVANTINA: WALL MOUNTED, ONE-PIECE QUARTZIA DECK -DECK COLOR: SNOWFALL -BOWL: CHINA SHELL CH-6360 UNDERMOUNT 18"x13" CHINA BOWL(S)	
19	LAVATORY DECK 3-STATION RIGHT TRASH	1/2" (1)	(1)	1 1/2"	1 1/2"	LEVANTINA	Q3303RT	-BASE: ACORN STAINLESS STEEL APRON: AP-3, 3 BOWL; - AP-3, 3 BOWL; AP-1, 1 BOWL; AP-2, 2 BOWL -CONTINUOUS WASTE PIPING AND P-TRAP.	
20	LAVATORY DECK 3-STATION LEFT TRASH		1/2" (3, T)	1 1/2"	1 1/2"	LEVANTINA	Q3303LT		
.21	LAVATORY DECK 3-STATION	1/2" (1)	1/2" (1)	1 1/2"	1 1/2"	LEVANTINA	Q3303LT	-FAUCET: TOTO TEL145-D10E - 0.5 GPM SENSOR OPERATED SELF- GENERATING POWER SYSTEM. CHROME PLATED BRASS P-TRAP	
22	LEFT TRASH LAVATORY DECK 1-STATION		1/2" (1)	1 1/2"	1 1/2"	LEVANTINA	Q3301	WITH CLEANOUT, GRID STRAINER WITH TAILPIECE. FOR L19/L21/L23/L25/27/29: (2) STOP VALVES PER DECK,	
23	LAVATORY DECK	1/2"	1/2"	1 1/2"	1 1/2"	LEVANTINA	Q3301	THERMOSTATIC MIXING VALVE KIT (TMV, HOSES & FITTINGS) SET TMV TO 105°F.	
24	1-STATION LAVATORY DECK 2-STATION	(1)	(1) 1/2" (2, T)	1 1/2"	1 1/2"	LEVANTINA	Q3302	FOR L18/L20/L22/L24/L26/L28: (1) STOP VALVE, (1) 3/8"x1/2" SS BRAIDED WATER SUPPLY PER FAUCET; TMV NOT REQUIRED.	
25	LAVATORY DECK	1/2"	1/2"	1 1/2"	1 1/2"	LEVANTINA	Q3302		
26	2-STATION LAVATORY DECK 2-STATION	(1)	(1) 1/2" (2, T)	1 1/2"	1 1/2"	LEVANTINA	Q3302T		
27	WITH TRASH LAVATORY DECK 2-STATION	1/2" (1)	1/2" (1)	1 1/2"	1 1/2"	LEVANTINA	Q3302T		
28	WITH TRASH LAVATORY DECK 1-STATION			1 1/2"	1 1/2"	LEVANTINA	Q3301	FOR L28/29: - LOW HEIGHT BASE ACORN 6213-100	
29	CHILD HEIGHT LAVATORY DECK 1-STATION	1/2" (1)	1/2" (1)	1 1/2"	1 1/2"	LEVANTINA	Q3301		
38	CHILD HEIGHT LAVATORY (ADA)		1/2" (T)	1 1/2"	1 1/2"	AMERICAN STANDARD	0321.075	FAUCET: TOTO TEL3LS-10 - 0.5 GPM SENSOR OPERATED SELF- GENERATING POWER SYSTEM, STANDARD SPOUT, 4" COVER PLATE, GRID STRAINER WITH TAILPIECE, P-TRAP WITH CLEANOUT, STOR VALVES SS BRAIDED WATER SURPLIES AND	
39	LAVATORY (ADA)	1/2"	·	1 1/2"	,	AMERICAN STANDARD	0321.075	STOP VALVES, SS BRAIDED WATER SUPPLIES AND ESCUTCHEONS. PROVIDE THERMOSTATIC MIXING VALVE FOR L39. CARRIER: JOSAM 17100, WADE W-520. LAVATORY ENCLOSURE: TRUEBRO LAV-SHIELD 2018 L39 ASSE 1070 THERMOSTATIC MIXING VALVE: ZURN ZW3870XLT SET TO 105°F.	A
VC1	ELECTRIC WATER COOLER	1/2"		1 1/2"	1 1/4"	OASIS	PG8AC	STAINLESS STEEL TOP AND CABINET, FRONT AND SIDE PUSH BARS, LEAD FREE, WATER SAVER BUBBLER WITH FLEXIBLE BUBBLER CHARD (FOR HALSEY TAXIOR SMARTELOW BUBBLER KIT) STOR VALVE	,
	(SINGLE)					HALSEY TAYLOR	HAC8FS-Q-ADA	GUARD (FOR HALSEY TAYLOR - SMARTFLOW BUBBLER KIT), STOP VALVE, 3/8"x1/2" SS BRAIDED WATER SUPPLY, P-TRAP WITH CLEANOUT AND ESCUTCHEON. CARRIER: JOSAM 17560-WC, WADE 400-AM11	
VC2	ELECTRIC WATER COOLER	1/2"		1 1/2"	1 1/4"	OASIS	PG8ACSL	STAINLESS STEEL TOP AND CABINET, FRONT AND SIDE PUSH BARS, MATCHING UPPER UNIT APRON, LEAD FREE, WATER SAVER BUBBLER	A
	(SPLIT-LEVEL)					HALSEY TAYLOR	HAC8FSBL-Q-ADA OR HAC8FSBLR-Q-ADA	WITH FLEXIBLE BUBBLER GUARD (FOR HALSEY TAYLOR — SMARTFLOW SMARTFLOW BUBBLER KIT), STOP, 3/8"x1/2" SS BRAIDED WATER SUPPLY, P—TRAP WITH CLEANOUT AND ESCUTCHEON. CARRIER: JOSAM 17560—WCBL, WADE 440—AM11	_
IB6	HOSE BIBB (FLUSH MOUNTED WALL BOX)	3/4"				ACORN WOODFORD BRADLEY	8151 B24 7910	POLISHED FINISH WITH STAINLESS STEEL OR CHROME HINGED BOX, INTEGRAL VACUUM BREAKER, AND LOOSE TEE KEY.	

GENERAL INFORMATION (ALL FIXTURES):

1. THIS SCHEDULE IS COMPREHENSIVE. ALL MARKS MAY OR MAY NOT BE USED ON THE PLANS.

2. SUBSTITUTIONS NOT PERMITTED. REF SPECIFICATIONS FOR APPROVED MANUFACTURERS OF THE FOLLOWING TRIM AND ACCESSORIES;

- P-TRAP WITH CLEANOUT PLUG AND SINK CONTINUOUS WASTES: POLISHED CHROME-PLATED TUBULAR BRASS, 17 GAUGE, WITH BRASS NUTS AND SLIP INSERTS.

- SS BRAIDED WATER SUPPLY: FLEXIBLE BRAIDED STAINLESS STEEL (SS) OUTER SHEATHING WITH REINFORCED PVC INNER TUBING. - STOP VALVES: CHROME PLATED BRASS, QUARTER TURN ANGLE STOP VALVES.

02.24.17

A. INSTALL FURNISHED 1/2" X 3 3/4" STAINLESS STEEL SIMPSON WEDGE-ALL WEDGE ANCHORS FOR ALL FIXTURE CARRIERS.

B. INSTALL FURNISHED THERMOSTATIC MIXING VALVE.

C. REFERENCE ARCHITECTURAL DRAWINGS FOR EWC2 ORIENTATION. D. COORDINATE WATER ROUGH-IN HEIGHT FROM MANUFACTURER'S INSTALLATION INSTRUCTIONS WITH GRAB BAR LOCATION. REF ARCH.

E. USE SAME MANUFACTURER FOR UR1 AND UR2.

JEFFERY DON FERGUSON, P.E. ENGINEER OF RECORD CA # F-2220

> **PLUMBING** SCHEDULES

CYNTERGY ENGINEERING, PLL 810 S CINCINNATI SECOND FLOOR TULSA, OK 74119

www.cyntergy.com

STIPULATION FOR REUSE

THIS DRAWING WAS PREPARED FOR USE ON A SPECIFIC SITE AT FORT WORTH, TX CONTEMPORANEOUSLY WITH ITS ISSUE DATE ON 02/12/18, AND IT IS NOT SUITABLE FOR USE ON A DIFFERENT PROJECT SITE OR AT A LATER TIME. USE OF THIS DRAWING FOR REFERENCE OR EXAMPLE ON ANOTHER PROJECT REQUIRES THE SERVICES OF PROPERLY LICENSED ARCHITECTS AND ENGINEERS. REPRODUCTION OF THIS DRAWING FOR REUSE ON ANOTHER PROJECT IS NOT AUTHORIZED AND MAY BE CONTRARY TO THE LAW.

ISSUE BLOCK

02/12/18 | PERMIT/ BID

30 X 42 SHEET SE

PROTO CYCLE: 12/29/17

DOCUMENT DATE: 02/12/18

DOCUMENTS WITHOUT SIGNATURE AND REQUIRED SEAL OF AOR/EOR ARE NOT FOR CONSTRUCTION

CHECKED BY:

DRAWN BY:

12.30.16

⁻ P-TRAP WITH CLEANOUT PLUG AND SINK CONTINUOUS WASTES: POLISHED CHROME-PLATED TUBULAR BRASS, 17 GAUGE, WITH BRASS NUTS AND SLIP INSERTS.

⁻ SS BRAIDED WATER SUPPLY: FLEXIBLE BRAIDED STAINLESS STEEL (SS) OUTER SHEATHING WITH REINFORCED PVC INNER TUBING. - STOP VALVES: CHROME PLATED BRASS, QUARTER TURN ANGLE STOP VALVES.

A. MOUNT EYEWASH 36" AFF TO TOP OF HEAD SPRAY. B. INSTALL MOP SINK FAUCET AT 32" AFF AND LOCATE TWO MOP HANGER BRACKETS SIDE BY SIDE NEAR MOP SINK.

C. INSTALL FURNISHED TMV UNLESS SERVED WITH TEMPERED WATER OR NOTED OTHERWISE ON PLUMBING DRAWINGS. SET AT 120° F.

D. TRIM WITH OFFSET TAILPIECE, 5/8" ARMAFLEX INSULATION ON EXPOSED HOT WATER AND DRAIN LINES. HOLD ALL EXPOSED PIPING HIGH AS POSSIBLE. E. REFER TO OWNER PROVIDED EQUIPMENT INFORMATION FOR ACTUAL ROUGH-IN HEIGHT REQUIREMENTS.

F. INSTALL FURNISHED THERMOSTATIC MIXING VALVE.

G. INSTALL FURNISHED 1/2" X 2 1/2" STAILESS STEEL SIMPSON WEDGE-ALL ANCHORS FOR ALL FIXTURES

H. CONTRACTOR TO COORDINATED THE REQUIRED CARRIER PRIOR TO ORDERING.