

SECTION 09655 - RESILIENT BASE AND ACCESSORIES

PART 1 - GENERAL

1.1 SUMMARY

A. Section Includes:

1. Resilient Base (B), furnished by Owner for installation by Contractor.
2. Plastic base (B), furnished by Owner for installation by Contractor.
3. Sanitary Cove Base (SCB), furnished by Owner for installation by Contractor.
4. Duratuff Base (DB), furnished by Owner for installation by Contractor.

B. Related Requirements:

1. Section 07900 – Joint Sealers: Sealant between bases and floor or wall surfaces.
2. Appendix A – Products and Work By Owner or Separate Contractor.
 - a. General procedures related to Owner furnished products.
 - b. Manufacturers, suppliers, vendor contacts and product names and numbers related to Owner furnished products.

1.2 DELIVERY, STORAGE AND HANDLING

- A. Transport, handle, store, and protect products in compliance with the requirements of Section 01600.
- B. Receive Owner Furnished products in accordance with the requirements of Section 01600.
- C. Product Delivery: Owner's Supplier will deliver Owner furnished products to site to be received by Contractor. Contact Owner's Supplier to coordinate product delivery and installation.
- D. Acceptance at Site: Inspect Owner furnished products upon delivery to Site to verify quantity, and report discrepancies in quantity delivered or damage.
- E. Product Packaging: Owner furnished products will be delivered in manufacturer's original packaging with identification markings on each component or package.

PART 2 - PRODUCTS

2.1 OWNER FURNISHED PRODUCTS

- A. Owner's Supplier will furnish the following as specified in Appendix A (Section 09655) for installation by Contractor.
 1. Bases.
 2. Base accessories.
 3. Base installation accessories: Adhesive/sealant and drill bits.
 4. Building tape.

2.2 CONTRACTOR FURNISHED PRODUCTS

A. Base Fasteners:

1. Plastic Base and Duratuff Plastic Base: Black flathead countersunk screws, length sufficient to penetrate substrate and metal stud wall framing.
2. Sanitary Cove Base: As indicated by the manufacturer's written instructions and as shown on Drawings.]

PART 3 - EXECUTION

3.1 INSTALLATION

A. Resilient Base:

1. Install base in accordance with manufacturer's requirements using manufacturer's approved adhesive.
2. Fit joints tight and vertical. Maintain minimum measurement of 18 inches between joints. Use premolded corner units.
3. Install base on solid backing. Bond tight to wall surfaces.
4. Scribe to fit door frames and other interruptions.
5. Remove excess adhesive from floor, wall surfaces and base.

B. Plastic Base (including Duratuff Plastic Base):

1. Fit joints tight and vertical. Maintain minimum measurement of 18 inches between joints
2. Install base on solid backing. Bond tight to wall and floor surfaces.
3. Scribe to fit door frames and other interruptions.
4. Miter and adhesively bond plastic base joints together.
5. Pre-drill plastic base and trim for attachment screws. Unless otherwise shown, attach plastic base at 24 inches on center into metal stud wall framing.

C. Sanitary Cove Base:

1. Install base in accordance with manufacturer's written instructions and as shown on the Drawings.

D. Building Tape: Install at base of wall or at joints as shown on the drawings. Install in accordance with manufacturer's instructions.

3.2 CLEANING

- #### A. Remove excess adhesive from floor, base, and wall surfaces without damage.

END OF SECTION