



**01 REFLECTED CEILING PLAN**  
 FILE NAME: H21.DWG  
 Scale: 1/4" = 1'-0" PLAN NORTH TRUE NORTH

- NOTES - REFLECTED CEILING PLAN**
- THE ARCHITECTURAL DRAWINGS SHOULD BE USED WITH AND IN CONJUNCTION WITH THE CIVIL, STRUCTURAL, MEP, FIRE PROTECTION DRAWINGS AND SPECIFICATIONS. THE GENERAL CONTRACTOR IS RESPONSIBLE FOR ALL COORDINATION BETWEEN THE DRAWINGS. DISCREPANCIES SHOULD BE BROUGHT TO THE ATTENTION OF GFF.
  - THE GENERAL CONTRACTOR IS ADVISED THAT THE AVAILABLE SPACE FOR ROUTING ALL ELECTRICAL, MECHANICAL, PLUMBING, FIRE PROTECTION AND COMMUNICATIONS PIPING CONDUIT, TRAYS AND DUCTWORK MAY BE MINIMAL IN MANY LOCATIONS. THE GENERAL CONTRACTOR SHALL COORDINATE ALL OF THE TRADES WORK.
  - VERIFY FIELD CONDITIONS AND LOCATIONS OF ALL PLUMBING, DUCTS, STRUCTURAL ELEMENTS, ETC., AND ARRANGE & MODIFY NON-VISIBLE ITEMS TO ENSURE ADEQUATE CLEARANCES FOR CEILING LAYOUT SHOWN.
  - ALL PENETRATIONS OF FIRE RATED ASSEMBLIES SHALL BE FIRE BLOCKED AND SEALED PER UL APPROVED METHODS.
  - THE GENERAL CONTRACTOR IS TO ENSURE THE CONTINUITY OF NEW OR EXISTING FIRE-RATED CONSTRUCTION.
  - ALL MANUFACTURER'S NAME, TRADEMARK, LOGOS, ETC SHALL NOT BE VISIBLE TO THE PUBLIC, UNLESS REQUIRED BY THE BUILDING CODE.
  - ALL CEILING MOUNTED ITEMS SHALL BE REINFORCED WITH BRACING, BLOCKING, AND/OR STRUCTURE AS REQUIRED. THE GENERAL CONTRACTOR SHALL BE RESPONSIBLE FOR DETERMINING THE SUPPORT REQUIRED TO MAINTAIN THE INTEGRITY OF THE CEILING AND THE SECURITY OF THE ITEM MOUNTED. THE GENERAL CONTRACTOR SHALL COORDINATE THE PLACEMENT OF ALL BLOCKING PRIOR TO CLOSING OF CEILING. ALL BLOCKING SHALL BE FIRE RETARDANT TREATED. USE OF COMBUSTIBLE MATERIALS ABOVE THE CEILING IS NOT PERMITTED.
  - PROVIDE FRAMING ABOVE CEILING WHERE WALLS DO NOT GO TO DECK FOR SUPPORT OF SUSPENDED ACOUSTICAL CEILING SYSTEM.
  - DO NOT SCALE DRAWINGS, WRITTEN DIMENSIONS GOVERN. IN CASE OF CONFLICT, NOTIFY GFF FOR WRITTEN CLARIFICATION PRIOR TO PROCEEDING.
  - DIMENSIONS SHOWN AS "V.I.F." SHALL BE VERIFIED IN THE FIELD. THE GENERAL CONTRACTOR SHALL NOTIFY GFF OF ANY DISCREPANCY IN DIMENSIONS PRIOR TO PROCEEDING WITH WORK IN THAT AREA.
  - DIMENSIONS MARKED "HOLD" SHALL BE MAINTAINED AND SHALL ALLOW FOR THICKNESS OF FINISHES. THE GENERAL CONTRACTOR SHALL NOT ADJUST DIMENSION WITHOUT WRITTEN INSTRUCTIONS FROM GFF.
  - THE LOCATIONS OF MECHANICAL, ELECTRICAL, AND FIRE PROTECTION ITEMS (I.E. CEILING MOUNTED DEVICES, SUCH AS STROBES, SPEAKERS, LIGHT FIXTURES, SPRINKLER HEADS, RETURN AND SUPPLY AIR GRILLES, SECURITY DEVICES, ETC.) ARE SHOWN FOR REFERENCE ONLY AND SHALL BE CONFIRMED WITH GFF IN THE FIELD PRIOR TO INSTALLATION. REFER TO MECHANICAL, ELECTRICAL AND FIRE PROTECTION DRAWINGS & SPECIFICATIONS FOR DESIGN OF THESE SYSTEMS. NOTIFY GFF OF ANY CONFLICTS PRIOR TO INSTALLATION.
  - SWITCHES SHOWN ADJACENT TO EACH OTHER SHALL BE GANGED AND COVERED WITH A SINGLE COVERPLATE. REFER TO ELECTRICAL DRAWINGS FOR SWITCH COVER PLATE SPECIFICATION. NOTIFY GFF OF ANY CONFLICTS PRIOR TO INSTALLATION.
  - COLOR OF ESCUTCHEON COVERS IN CEILINGS WILL BE SELECTED BY GFF.
  - THE GENERAL CONTRACTOR SHALL PROVIDE ACCESS PANELS AT ALL CONCEALED MECHANICAL, PLUMBING, AND ELECTRICAL ITEMS WHICH REQUIRE SERVICE OR ACCESS. ACCESS PANELS IN RATED CEILINGS SHALL HAVE THE SAME RATING AS THE ASSEMBLY THEY ARE IN.
  - ALL CEILING MOUNTED DEVICES, SUCH AS LIGHT FIXTURES, FIRE ALARM STROBES, OCCUPANCY SENSORS, SPEAKERS, RETURN AND SUPPLY AIR GRILLES, SECURITY DEVICES, ETC. TO BE CENTERED IN TILE, UNO.
  - ALL CEILING HEIGHTS TO BE 8'-0" AFF, UNO.
  - ALL FIRE PROTECTION ITEMS (SPRINKLER HEADS) TO BE CENTERED IN THE CEILING TILE (BOTH WAYS), UNO.
  - THE LIGHTING LAYOUT AND TYPES SHALL MEET ALL ENERGY CODE REQUIREMENTS OF THE AUTHORITY HAVING JURISDICTION.
  - PROVIDE SHOP DRAWINGS AND PRODUCT SUBMITTALS FOR ALL LIGHT FIXTURES, FIRE ALARM STROBES, FIRE/LIFE/SAFETY DEVICES, SECURITY DEVICES, SPEAKERS, ETC. PRIOR TO ORDERING, FABRICATION, AND INSTALLATIONS. IT IS THE CONTRACTOR'S RESPONSIBILITY TO PROVIDE SUBMITTALS IN A TIMELY MANNER TO ALLOW FOR CORRECTIONS OR REJECTIONS WITHOUT CAUSING DELAY TO THE PROJECT SCHEDULE.

- KEY NOTES - REFLECTED CEILING PLAN**
- EXISTING SKYLIGHT, TYPICAL.
  - EXPOSED CEILING TO UNDERSIDE OF ROOF DECK; ALL NEW ELECTRICAL WIRING, ELECTRICAL ACCESSORIES, DATA CABLE, DATA CABLE ACCESSORIES, DUCTWORK, MECHANICAL ITEMS SHALL BE INSTALLED IN A NEAT AND ORDERLY MANNER. EXPOSED CEILING AREAS (INCLUDING ALL ABOVE CEILING ITEMS) TO BE PAINTED (P-1).
  - ADJUST FIXTURE LOCATIONS IN FIELD AS NECESSARY. INTENT IS TO CENTER CLUSTER OF FIXTURES OVER RECEPTION DESK.
  - CENTER FIXTURE / TRACK IN ROOM.

**LEGEND - REFLECTED CEILING PLAN**

SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION
[Hatched Area]	AREA NOT IN SCOPE, UNO	A	SUSPENDED DOWNLIGHT, LED - 10'-0" AFF
[Stippled Area]	GYPSUM CEILING BOARD, P-1, SHERWIN WILLIAMS	⊙	TRACK ACCENT SPOT LIGHT, LED - 10'-0" AFF
[C-1]	OPEN TO STRUCTURE, PAINTED PT-2	F	SUSPENDED LINEAR, LED - 10'-0" AFF
[Square]	DETAIL MARKER	---	LED UNDER-CABINET LIGHTING
[Dashed Line]	CENTERLINE	⊕	VARIOUS SUSPENDED DECORATIVE PENDANTS, LED - REFER 02-700 FOR MOUNTING HEIGHTS (TO BOTTOM OF FIXTURE)
(B)	DENOTES EXISTING ITEM TO REMAIN	⊗	SPEAKER, DECK-MOUNTED, ROUTE CONTROLS TO STORAGE 103A

**LEGEND - REFLECTED CEILING PLAN**

SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION
[Hatched Area]	AREA NOT IN SCOPE, UNO	A	SUSPENDED DOWNLIGHT, LED - 10'-0" AFF
[Stippled Area]	GYPSUM CEILING BOARD, P-1, SHERWIN WILLIAMS	⊙	TRACK ACCENT SPOT LIGHT, LED - 10'-0" AFF
[C-1]	OPEN TO STRUCTURE, PAINTED PT-2	F	SUSPENDED LINEAR, LED - 10'-0" AFF
[Square]	DETAIL MARKER	---	LED UNDER-CABINET LIGHTING
[Dashed Line]	CENTERLINE	⊕	VARIOUS SUSPENDED DECORATIVE PENDANTS, LED - REFER 02-700 FOR MOUNTING HEIGHTS (TO BOTTOM OF FIXTURE)
(B)	DENOTES EXISTING ITEM TO REMAIN	⊗	SPEAKER, DECK-MOUNTED, ROUTE CONTROLS TO STORAGE 103A

No.	Date	Revision

